

# TCE 4230

## Swing Arm Tire Changer



**BOSCH**  
Invented for life



### A proven swing arm changer with 26" outside clamping capacity without the need for adapters.

The TCE 4230 SFA handles passenger vehicles rims with external clamping up to 26", and accommodates tires up to 44" in diameter.

The following arm ensures that the top bead remains in the drop center when mounting and demounting difficult tires, and prevents accidental bead reseating.

The TCE 4230 is also available without the articulating following arm.

## Features



The pneumatic following arm assists in mounting and demounting low profile tires.



Replaceable plastic inserts protect the rim surface from metal contact to prevent accidental damage.



Telescoping adjustments on the bead breaker shaft increase wheel width and tire diameter capacities.



### Essential Features:

- ▶ Maximum rigidity and turntable torque
- ▶ High performance mount/demount head with tire iron slot, ideal for mounting low profile tires
- ▶ Optional helper arm assists with mounting of low profile tires
- ▶ Non-opposing adjustable jaws with inflation jets
- ▶ 3-position bead breaker with telescoping adjustment

The TCE 4230 Swing Arm Tire Changer is also available without the following arm by ordering part number F00E900667.

F00E900667 TCE 4230 S30 SFA Swing Arm Tire Changer with Articulating Following Arm  
 F00E900668 TCE 4230 S30 Swing Arm Tire Changer

Specifications			
Inside Clamping	12"-28"	HP Motor	1
Outside Clamping	10"-26"	Electric Requirement	120 V 20 A, NEMA 5-15P
Rim Width*	15"	Weight	700 lbs
Tire Diameter**	44"	Width	37"
Bead Breaker Capacity	18"	Depth	37.5"
Air Pressure	120-170 lbs	Height	74"

\*Rim Width is dependent on rim offset  
 \*\*Tire Diameter is dependent on tire width