

TCE 4335

High Performance Tire Changer



BOSCH
Invented for life



A high-end, manual, tilt-tower tire changer with maximum rigidity.

The TCE 4335 THP is a high end, manual, tilt-tower changer with outside clamping up to 26".

The powerful, dual-cylinder pneumatic mounting helper system offers three points of contact and makes mounting and demounting low profile tires stress free.

The heavy tower and cabinet provide maximum rigidity and saves tires from damage by eliminating tower flex.

Features



Replaceable plastic inserts protect the rim surface from metal contact to prevent accidental damage.



Powerful, dual-cylinder pneumatic mounting helper system makes mounting and demounting low-profile tires stress free.



Non-opposing adjustable jaws with built-in inflation jets feature embossed dimensions for faster and more accurate clamping.



Essential Features:

- ▶ Provides outside clamping up to 26"
- ▶ Non-opposing adjustable jaws for faster and more accurate rim clamping
- ▶ Dual cylinder pneumatic mounting helper system on THP model
- ▶ 3-position bead breaker with telescoping adjustment
- ▶ Inflation jets built into clamps ensure correct positioning
- ▶ THP model is ideal for servicing Tire Pressure Monitoring Systems (TPMS)

The TCE 4335 High Performance Tire Changer is also available without the following arm by ordering part number F00E900669.

- F00E900669 TCE 4335 S30 High Performance Tire Changer
- F00E900670 TCE 4335 S30 THP High Performance Tire Changer with Mounting Helper System
- SM101608 Replaceable plastic inserts
- SM104071 Standard jaw protectors

Specifications			
Inside Clamping	12"-28"	HP Motor	1
Outside Clamping	10"-26"	Electric Requirement	120 V 20 A, NEMA 5-15P
Rim Width*	15"	Weight	750 lbs
Tire Diameter**	40"	Width	40"
Bead Breaker Capacity	18"	Depth	47"
Air Pressure	120-170 lbs	Height	72"

*Rim Width is dependent on rim offset

**Tire Diameter is dependent on tire width