

TCE 4540

Center Post Hydraulic Leverless Tire Changer



BOSCH

Invented for life



No more tire lever! The TCE 4540 eliminates the tire lever while changing a tire and nothing touches the wheel.

Versatile center post design tire changer accommodates rims up to 30" in diameter. Dual clamping rollers effortlessly loosen tire beads and quickly perform tire to wheel matching. Easy to use control panel is integrated for simple and accurate tool operation. Improved center clamping system safely secures rim to base of clamping system

No Tire Lever Required!


Features



No bulky tire lever – the unique mounting hook effortlessly secures and lifts the top bead of the rim. The bead gently glides off the rim as the turntable rotates.



The air-operated following arm travels with the tire, keeping the top bead in the drop center for trouble-free mounting.



The integrated wheel lift with roller system raises the wheel onto the turntable. The turntable gently lowers the wheel on the center post for quick and accurate clamping.



Essential Features:

- ▶ Leverless mounting and demounting
- ▶ Capable of handling up to 30" rim diameter including run-flats and low profile tires
- ▶ Accommodates tires up to 44" in diameter
- ▶ Robust and dependable hydraulic fluid mount/demount system
- ▶ Dual clamping bead rollers with exclusive hydraulic performance
- ▶ Center post clamping design
- ▶ Integrated control panel
- ▶ Integrated wheel lift with roller system
- ▶ Convenient tool storage tray

The TCE 4540 offers 3 points of contact mount low profile and run flat tires with ease.

Accessories



Recommended optional Reverse Drop Center Adapters for properly changing reverse drop center wheels.

- 5-Lug adapter – part #1690XXXXXX
- 6-Lug adapter – part #1690XXXXXX (shown)
- 8-Lug adapter – part #1690XXXXXX
- Complete Reverse Drop Center Adapter Kit, part #1690XXXXXX

F00E900673 TCE 4540 S30 Center Post Hydraulic Leverless Tire Changer

Specifications			
Inside Clamping	8"–31.5"	HP Motor	2
Outside Clamping	8"–31.5"	Electric Requirement	220 V 1ph, NEMA L6-20P
Rim Width*	22"	Weight	1400 lbs
Tire Diameter**	60"	Width	60"
Bead Breaker Capacity	22"	Depth	65"
Air Pressure	120–170 lbs	Height	72"

*Rim Width is dependent on rim offset
 **Tire Diameter is dependent on tire width